Attachment C Annual Fugitive Emissions Monitoring Report



Dominion

Loudoun LDAR

Initial Annual Report NSPS Subpart OOOOa PERIOD: 3/7/2019 - 8/2019

Prepared By:

Target Emission Services

800 Town and Country Blvd. (Suite 300) Houston, Texas, 77024

WWW.TARGETEMISSION.COM

Report Generated on: Sep 16, 2019



District: Facility Name:	DETI-	Eastern	Regulation(s):		NSPS Subpart 0000	3
	Facility Name: Loudo		Regulation(s): Report Date: Period:	NSPS Subpart 0000a		
CDC Count					Sep 16, 2019	2019-Aug-01
GPS Coord. 38.995854 This report satisfies the requirement		-77.591168		2018-Aug-02	TO TO	
This report satis	fies the requirement	s of 40 CFR §60.5420a(b)(7) for the collection of fugitive	ve emissions components at	the above referenced comp	ressor station.
	In	formation required to	be reported per §	60.5420a(b)(7)(i) - (vi)	
Monitoring Q		Q2	Q3			
Survey Start Date/Time		04/25/2019 1:30 PM	survey conducted after report date	NOTE - the new compress no survey was required for	or (Unit 4) first operated on Q1 (within 60 days of startu	March 7, 2019. As a re
Survey End Date/Time		04/25/2019 4:00 PM				
OGI Techni (see Appendix for OGI Technician T		Evan Musselman				
Ambient Ten	np. (°F)	60				
Sky Condit	tions	Partly Cloudy, 10%-50% sky is clouds				
Max. Wind Spe	ed (MPH)	1				
LDAR Instru	ument	Optical Gas Imaging/GFX- 320				
§60.5420a(b)(7)(vi) D Monitoring		No deviations from the Monitoring Plan				
Deviation(s) Ex	planation	N/A				
	§60.5420a(b)(7)(vii) - Number and type	of components for wi	hich fugitive emissions	were detected	
Valves		1				
Connecto		6				
Pressure Relief Devices Open-Ended Lines						
Flange	The state of the s					
Compress	iors	60				
Instrume						
Meters		0				
Other		7				
Total No. of Leak §60.5420		er and type of fugitive e	missions components	s that were not repaire	d as required in §60.53	397a(h)
Valves						
Connect						
Pressure Relie				-		
Open-Ended		8	h			
Flange		8				
Instrume		NI				
Meters					es bescheska japosa et .	
0.5420a(c)(15)(ii)(l)(7) - Number and typ	e of components that w	ere tagged as a result §60.5397a(h)(3)(ii).	of not being repaired	during the monitoring	survey as require
Valve		1				
Connect		6				
Pressure Relie	ASSESSMENT OF THE PARTY OF THE	M.				
Flange	THE RESIDENCE OF THE PARTY OF T					
Compres						
Instrume						
Meter	•					
Othe						THE RESERVE OF THE PERSON NAMED IN
STATE OF THE PARTY	CHARLES OF A STREET STATES	er and type of difficult-to	-monitor and unsafe-	to-monitor fugitive emi	ssion components mo	initorea
Valve		100 100				
Pressure Relief Devices						
Open-Ended Lines						
Flanges						
Compressors						
Instruments		189				
Meter		109				
		.5420a(b)(7)(x) - Date of succes				



Fugitive Emissions Components Placed on DOR

This summary satisfies the annual reporting requirements of §60.5420a(b)(7)(xi), "number and type of fugitive emission components placed on delay of repair and explanation for each delay of repair".

		Compone	ent		
Quarter	Q2	N/A	N/A	N/A	N/A
Survey Date	04/25/19				
Valves	1				
Connectors	4				
Pressure Relief Devices					
Open-Ended Lines					
Flanges					
Compressors					
Instruments					
Meters					
Other					
Total No. of Leaks on DOR					
Date Surveyed	Emission ID	Component Type	Current Repair Status	Delay of Repair Explanation / Justification	
2019-04-25	26410113	Connector	Delay of Repair	Shutdown required	
2019-04-25	26410114	Valve	Delay of Repair	Shutdown required	
2019-04-25	26410117	Connector	Delay of Repair	Shutdown required	
2019-04-25	26410118	Connector	Delay of Repair	Shutdow	n required
2019-04-25	26410119	Connector	Delay of Repair	Ot	her



Fugitive Emissions Components Repaired During Reporting Period

This summary satisfies the annual reporting requirements of §60.5420a(b)(7)(x), "date of successful repair of the fugitive emission component" and §60.5420a(b)(7)(xii), "type of instrument used to resurvey a repaired fugitive emissions component that could not be repaired during the initial fugitive emissions finding".

Date Surveyed	Emission ID#	Date of Successful Repair	Repair Confirmation Method / Instrument
2019-04-25	26410112	2019-May-17	Snoop
2019-04-25	26410115	2019-May-17	Snoop



OGI Technician Training and Experience

Monitoring surveys are performed by personnel that are trained in the proper operation of the OGIC (Optical Gas Imaging Camera) to be used in the monitoring survey and that have prior experience using OGICs for the purposes of identifying fugitive emissions. Additionally, monitoring personnel are familiar with the types of equipment located at a natural gas compressor station. All monitoring personnel review each site specific monitoring plan prior to performing monitoring surveys at the Facility.

All Monitoring Technicians follow a protocol containing technical procedures, training requirements, and individual and team performance audits. This protocol ensures that each crew member follows a prescriptive training program. The training program includes minimum required field times for each module. Each module uses both written testing and on-site work performance audits to evaluate the crew member on their work performance.

Each crew member must successfully complete their training modules to be allowed to work as a member of the main field crew. The protocol also includes an audit program to evaluate work performance on an on-going basis. This system ensures that each crew member is adhering to the procedures and guidelines of the protocol.

Each monitoring technician:

- 1) holds a strong knowledge of oil and gas operations and has a detailed understanding of the various processes that are involved in the transportation and processing on natural gas.
 - 2) is trained (certified) and experienced in the use of fugitive emission detection and measurement equipment;
- has a minimum of 1000 hours of experience on the use of optical gas imaging, ultrasonic leak detection and emission flow rate measurement
 - 4) maintains required safety training and strong understanding of applicable TARGET Safe Operating Procedures; and
 - 5) received performance audits to ensure compliance to our prescriptive fugitive emission assessment protocol

The protocol contains technical procedures, training requirements, and individual and team performance audits. The purpose of our assessment protocol is to:

- 1) Maintain a high degree of Quality Control:
- 2) Ensure that all sources of fugitive emissions are identified;
- Ensure that all source data is consistently recorded to provide reliable and effective emission reduction recommendations.

This protocol eliminates the common problems and barriers that cause many programs to fail. Our staff are trained and audited to avoid many of the common fugitive emission program problems. Some of these common problems include:

- · Inexperienced with camera use and the concepts of infrared thermography
- · Not using multiple camera angles
- · Constantly moving the camera from scene to scene without pausing in each view to look for gas images
- · Many leaks are missed by relying solely on the automatic mode (manual mode can be more effective in certain situations)
- · Scanning too fast and missing components

Accurate data collection and entry is crucial to maintaining an effective Fugitive Emission Management Program. The data management protocol includes a data QA/QC review process that contains three levels of evaluation:

- 1) Technician Self Check at the end of each assessment the technician must review each emission entry to locate and remediate any data inconsistencies
- Team Lead Review at the end of each work day the Team Lead will run a QA/QC evaluation on each assessment and emission to ensure that data has been entered following the TARGET Protocol.
- Project Manager Evaluation on a weekly basis the project manager will run all emission data through a QA/QC data evaluation to detect and eliminate any inconsistencies.

APPENDIX



OGI Technician Training and Experience

Survey Date	OGI Technician	Certification Date	Months of OGI Experience
2019-Apr-25	Evan Musselman	2018-Jul-15	10

APPENDIX